

General Purpose Perforated Worm-Gear Hose Clamps

Breeze Liner


An integral extension of the band as an inner liner protects soft-surface hose (silicone and others) from damage caused by extrusion or shearing through the band slots. Liner clamps afford maximum protection to soft hoses while providing a true concentric seal.

Standard 1/2" (12.7mm) band
5/16" (7.9mm) slotted hex head screw

Per SAE standard J1508 Type "F"



SAE Size	EFFECTIVE DIAMETER RANGE				PART NUMBERS	
	Min.		Max.		Plated Hex Screw	410 SS Hex Screw
	in.	mm	in.	mm		
06	7/16	11	25/32	20	9206	9406
08	1/2	13	29/32	23	9208	9408
10	9/16	14	1-1/16	27	9210	9410
12	11/16	17	1-1/4	32	9212	9412
16	13/16	21	1-1/2	38	9216	9416
20	13/16	21	1-3/4	44	9220	9420
24	1-1/16	27	2	51	9224	9424
28	1-5/16	33	2-1/4	57	9228	9428
32	1-9/16	40	2-1/2	64	9232	9432
36	1-13/16	46	2-3/4	70	9236	9436
40	2-1/16	52	3	76	9240	9440
44	2-5/16	59	3-1/4	83	9244	9444
48	2-9/16	65	3-1/2	89	9248	9448
52	2-13/16	71	3-3/4	95	9252	9452
56	3-1/16	78	4	102	9256	9456
60	3-5/16	84	4-1/4	108	9260	9460
64	3-9/16	91	4-1/2	114	9264	9464
72	4-1/8	105	5	127	9272	9472
80	4-5/8	117	5-1/2	140	9280	9480
88	5-1/8	130	6	152	9288	9488
96	5-5/8	143	6-1/2	165	9296	9496
104	6-1/8	156	7	178	92104	94104



Note: Size 88, 96 & 104 will be supplied with a 9/16" (14.2 mm) band