

General Purpose Perforated Worm-Gear Hose Clamps

Breeze Mini

A lightweight, streamlined clamp generally used in small diameter applications such as air & fuel lines. The streamlined configuration allows for installation in tight fitting or difficult to reach areas. This clamp creates high sealing pressure with only 10 to 15 in./lbs. of installation torque.

5/16" (7.9 mm) band
 1/4" (6.4 mm) slotted hex head screw

Per SAE standard J1508 Type "M"



| SAE Size | EFFECTIVE DIAMETER RANGE | | | | PART NUMBERS | | | |
|----------|--------------------------|-----|--------|----|------------------|------------------|------------------|------------|
| | Min. | | Max. | | Plated Hex Screw | 410 SS Hex Screw | 300 SS Hex Screw | All 316 SS |
| | in. | mm | in. | mm | | | | |
| 4 | 7/32 | 5.6 | 5/8 | 16 | 3504 | 3604 | 3704 | 3804 |
| 6 | 7/16 | 11 | 25/32 | 20 | 3506 | 3606 | 3706 | 3806 |
| 8 | 1/2 | 13 | 29/32 | 23 | 3508 | 3608 | 3708 | 3808 |
| 10 | 9/16 | 14 | 1-1/16 | 27 | 3510 | 3610 | 3710 | 3810 |
| 12 | 11/16 | 17 | 1-1/4 | 32 | 3512 | 3612 | 3712 | |
| 16 | 15/16 | 24 | 1-1/2 | 38 | 3516 | 3616 | 3716 | |
| 20 | 1-3/16 | 30 | 1-3/4 | 44 | 3520 | 3620 | 3720 | |
| 24 | 1-7/16 | 37 | 2 | 51 | 3524 | 3624 | 3724 | |
| 28 | 1-11/16 | 43 | 2-1/4 | 57 | 3528 | 3628 | 3728 | |
| 32 | 1-15/16 | 49 | 2-1/2 | 64 | 3532 | 3632 | 3732 | |

